

General Information

Owners	Ocean Breeze PTE LTD
Year Built	2008
Shipyard	New Times Shipbuilding, China
Flag	Singapore
Class/Notation	American Bureau of Shipping *A1, Chemical Carrier, Oil Carrier, (e), ESP, *AMS, *ACCU, VEC, FL 30, SH, SHCM, PMP+ RRDA, UWILD
Vessel Type	Oil / Chemical Tanker (double hull)
IMO/LR No.	9407275
Call Sign	9V9423
Official No.	403473
Telephone	VSat Bridge: + 47 23398582 Certus: +870-7739 43 151
E-mail	master.Fuyo(at)jacob-vessel.com

Dimensions

Summer Deadweight	73,666 tons
Light Ship Weight	17,987 mt
Length o.a.	228,60 m
Length b.p.	219,70 m
Breadth moulded	32,26 m
Depth moulded	20,80 m
TPC	67,1 mt
Tonnage	22,454 NT / 42,010 GT

Propulsion and Aux Machines

Main Engine	Doosan Engine 7,888kW
Propeller	4 blade, solid, ABS 4 Ni-Al Bronze, dia 7,200 mm,
Aux Engine	3 x Yanmar 8N21L-EV; 970 kw
Boilers	2 x 20T/H Oil-fired Auxiliary Boiler Aalborg Industries

Capacity of Bunkers / Fresh Water

Bunker Capacity	Fuel Oil: 1.610,47 m ³
98 %	Diesel: 816,50 m ³
Fresh water Capacity	353,10 m ³
100 %	

Cargo and Ballast System

No. of Cargo Tank	12
Slop Tanks	2
Coating	1 ROT fully coated – pure epoxy
No. of segregations	3
Total cubic capacity at 98% (incl. Slops)	84,454,58 m ³
ROT Capacity	319,14 m ³
No. of Cargo Pumps	3 x 2300 m ³ /hr
Type of Cargo Pumps	Centrifugal
Discharge Capacity	6.900 m ³ /h
Vessel equipped with	IGS / SBT / COW
No. of SBTs	14
Capacity of SBT	25,283.02 m ³ at 100 %
Ballast Pumps	2 x 1,500 m ³ /hr
Type of Ballast Pumps	Centrifugal
Cargo Hoses Cranes	1 x 15 Tons SWL
Cargo Manifolds	3 X 16" ANSI 150 PSI
Cargo Heating	Steam, coils of stainless steel, max temp 66°C

Mooring Arrangement

<i>Mooring Winches</i>	
Forecastle	2 (double drums), brake capacity: 48 MT
Main Deck Forward	1 (double drum), brake capacity: 48 MT
Main Deck Aft	1 (double drum), brake capacity: 48 MT
Poop Deck	2 (double drum), brake capacity: 48 MT
<i>Mooring Wires</i>	
Forward	6 x 210 mtr, dia 30 mm
Aft	6 x 210 mtr, dia 30 mm (64.0 t)
<i>Bow Stoppers</i>	
	2 pcs, SWL 200 MT, 76mm ø
<i>Chocks</i>	
	2 pcs, 600 x 450 mm each
<i>Emergency towing;</i>	
	Chafe chain and tongue stopper